HOMESYSTEM

QUICK USER GUIDE

Remotec ZXT-600

Z-Wave Plus to IR bridge for split air conditioners

Manufacturer: **Remotec** · Model: **Remotec ZXT-600 AC Master**

PRODUCT IN THE HOMESYSTEM E-SHOP

obchod.homesystem.sk/en/remotec-z-wave-ovladac-klimatizacie/

This guide belongs to a product bought at obchod.homesystem.sk. Scan the QR code for current information, accessories and advice.

A Z-Wave Plus infrared controller for split air conditioners with a temperature sensor and thermostat function. It has built-in and cloud IR code libraries and backup of learned IR codes. It works as a slave dependent on a controller.

KEY FACTS

Model	ZXT-600 (BW8490)
Wireless	Z-Wave Plus (EU 868.4 MHz); secure inclusion, Classic and NWI; range up to 132 ft (~40 m) outdoors
Power supply	USB 5 V / 1 A or 2× AA alkaline (batteries and adapter not included)
Mode	battery = FLiRS, USB = always listening; set by the first power source, changing needs an exclusion
Inputs and outputs	PROG button; green/red LED; micro USB; telephone jack
Temperature	measuring 0–40 °C, step 0.5 °C, offset ±5 (parameter 37)
Size / weight	128 × 78 × 22 mm; 84 g without batteries
Environment	0–40 °C, non-condensing humidity; storage −10 to 50 °C
Certifications	FCC Part 15 Class B, IC, Z-Wave Plus
Warranty	1 year

SAFETY INSTRUCTIONS

WARNING

- Use new batteries of the correct type, do not mix them and remove them if unused for a long time. Do not burn batteries.
- Do not modify the device – risk of fire, electric shock or burns. It has no user-serviceable parts.
- Do not dispose of as household waste.

INSTALLATION

- On a wall at about 1.5 m, with free air circulation; not near heat, in sunlight, in a draught or in a recess.
- You need a Phillips screwdriver, a drill (3/16" for drywall, 7/32" for plaster), anchors and screws.

PROG BUTTON

PROG 3× within 1 s	inclusion (the controller must be in inclusion mode)
Hold PROG 3 s	reset: green is on; keep holding until green flashes twice

INDICATOR (LED)

🟢 **2× green**	inclusion succeeded
🔴 **2× red**	inclusion failed

FIRST SETUP

1. Insert batteries or connect USB – the first source sets the mode. Running an exclusion first is recommended.
2. Put your Z-Wave controller into inclusion mode.
3. Click the PROG button three times within 1 s. Success = 2× green, failure = 2× red.

Disposal: A product marked with the crossed-out wheelie bin symbol must not be put in household waste. Hand it in at an electronic-waste collection point or to the seller when buying a new device. Hand in batteries separately at a battery collection point.
Important: this short guide in English was prepared by HomeSystem s.r.o. for customers of the obchod.homesystem.sk e-shop based on the manufacturer's documentation. In case of differences, the manufacturer's original manual prevails: https://remotec.com.hk/wp-content/uploads/2022/03/Remotec_ZXT-600_Users-Manual-3417624.pdf
Product: obchod.homesystem.sk/en/remotec-z-wave-ovladac-klimatizacie/ · Status: 11/2026
Need help? obchod.homesystem.sk · +421 948 213 492